Printing date 06.03.2018 Version number 20 Revision: 06.03.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: EP Rostlöser ICE

· Article number: 9799000047

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Lubricant

• 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

· EUROPART Holding GmbH

· Martinstraße 13

· 58135 Hagen-Haspe

· Telefon: +49 2331 3564 0

· Telefax: +49 2331 3564 91499

· E-Mail: info@europart.net · Internet: www.europart.net

·1.4 Emergency telephone number: +49 2331 3564 0

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



· Hazard-determining components of labelling:

propan-2-ol

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

(Contd. on page 2)

Printing date 06.03.2018 Version number 20 Revision: 06.03.2018

Trade name: Rust Shock Spray

	(Contd. of page 1)
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing vapours or spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear eye protection / face protection.
P305+P351+P33	38 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501	Dispose of contents/container to hazardous or special waste collection point.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- **PBT:** Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

CAS: 75-28-5	isobutane	25-<50%
EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	♦ Flam. Gas 1, H220; ♦ Press. Gas (Comp.), H280	
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H33	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	20-<25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane Flam. Gas 1, H220; Press. Gas (Comp.), H280	5-<10%

· Regulation (EC) No 648/2004 on detergents / Labelling for contents aliphatic hydrocarbons ≥30%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- After inhalation:

Supply fresh air; consult doctor in case of complaints.

Take affected persons into fresh air and keep quiet.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately remove any clothing soiled by the product.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: Do not induce vomiting; call for medical help immediately.

(Contd. on page 3)

Printing date 06.03.2018 Version number 20 Revision: 06.03.2018

Trade name: Rust Shock Spray

(Contd. of page 2)

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- **Suitable extinguishing agents:**

Foam

Fire-extinguishing powder

Carbon dioxide

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

• **6.4 Reference to other sections** See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin and eyes.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

GB

Printing date 06.03.2018 Version number 20 Revision: 06.03.2018

Trade name: Rust Shock Spray

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Ingre	· Ingredients with limit values that require monitoring at the workplace:	
CAS:	67-63-0 propan-2-ol	
	Short-term value: 1250 mg/m³, 500 ppm	
	Long-term value: 999 mg/m³, 400 ppm	
CAS:	106-97-8 butane	
WEL	Short-term value: 1810 mg/m³, 750 ppm	
	Long-term value: 1450 mg/m³, 600 ppm	
	Carc (if more than 0.1% of buta-1.3-diene)	

- · **Additional information:** The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- **Respiratory protection:** Not necessary if room is well-ventilated.
- Recommended filter device for short term use: Filter AX
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Butyl rubber, BR

Recommended thickness of the material: $\geq 0.5 \text{ mm}$

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol Colour: Blue · Odour: Like alcohol

· Change in condition

Melting point/freezing point: Undetermined.

(Contd. on page 5)

Printing date 06.03.2018 Version number 20 Revision: 06.03.2018

Trade name: Rust Shock Spray

	(Contd. of page
Initial boiling point and boiling ra	ange: Not applicable, as aerosol.
· Flash point:	Not applicable, as aerosol.
· Ignition temperature:	>200 °C
· Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
· Density at 20 °C:	0.61793 g/cm³
· Solubility in / Miscibility with	
water:	Fully miscible.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Organic solvents:	94.9 %
VOC (EC)	586.4 g/l
Solids content:	0.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values re	levant for	classification:
-----------	-----------	------------	-----------------

ATE (Acute Toxicity Estimates)

Inhalative LC50/4 h 89.6 mg/l (rat)

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

GB

Printing date 06.03.2018 Version number 20 Revision: 06.03.2018

Trade name: Rust Shock Spray

(Contd. of page 5)

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European	· European waste catalogue	
16 05 04*	16 05 04* gases in pressure containers (including halons) containing hazardous substances	
15 01 04	metallic packaging	

- · Uncleaned packaging:
- · **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number	
· ADR/RID/ADN, IMDG, IATA	UN1950

 \cdot 14.2 UN proper shipping name

· ADR/RID/ADN UN1950 AEROSOLS · IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- · ADR/RID/ADN



• Class 2 5F Gases. • Label 2.1

· IMDG, IATA



· Class 2.1

(Contd. on page 7)

Printing date 06.03.2018 Version number 20 Revision: 06.03.2018

Trade name: Rust Shock Spray

14.4 Packing group ADR/RID/ADN, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: No 14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Code Sw1 Protected from sources of heat. Sw22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity abov 1 litre: Category B. For WASTE AEROSOLS: Categor C, Clear of living quarters. Segregation Code Segregation Code Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with capacity above 1 litre: Segregation as for the appropriat subdivision of class 2. For WASTE AEROSOLS Segregation as for the appropriate subdivision of class 2. 14.7 Transport in bulk according to Anne x II of Marpol and the IBC Code Transport/Additional information: ADR/RID/ADN Limited quantities (LQ) Limited quantities (EQ) Not permitted as Excepted Quantity Transport category 2 Tunnel restriction code D IMDG Limited quantities (LQ) LiL Excepted quantities (EQ) Not permitted as Excepted Quantity Limited quantities (LQ) LiL Excepted quantities (EQ) Not permitted as Excepted Quantity		(Contd. of page
ADR/RID/ADN, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: No 14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity abov 1 litre: Category B. For WASTE AEROSOLS: Categor C, Clear of living quarters. Segregation Code SG69 For AEROSOLS with a maximum capacity of litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with capacity above 1 litre: Segregation as for the appropriat subdivision of class 2. For WASTE AEROSOLS with capacity above 1 litre: Segregation as for the appropriat subdivision of class 2. For WASTE AEROSOLS Segregation as for the appropriate subdivision of class 2. 14.7 Transport in bulk according to Anne x II of Marpol and the IBC Code Not applicable. Transport/Additional information: ADR/RID/ADN Limited quantities (LQ) Limited quantities (EQ) Code: E0 Not permitted as Excepted Quantity Transport category 2 Tunnel restriction code DMDG Limited quantities (LQ) LL Excepted quantities (LQ) LL Excepted quantities (LQ) LL Excepted quantities (LQ) LC Code: E0 Not permitted as Excepted Quantity	Label	2.1
Marine pollutant: 14.6 Special precautions for user Danger code (Kemler): EMS Number: EMS Number: Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity abov 1 litre: Category B. For WASTE AEROSOLS: Categor C, Clear of living quarters. Segregation Code Segregation Code Segregation Code Segregation Code Segregation Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with capacity above 1 litre: Segregation as for the appropriat subdivision of class 2. For WASTE AEROSOLS Segregation as for the appropriate subdivision of class 2. 14.7 Transport in bulk according to Anne x II of Marpol and the IBC Code Transport/Additional information: ADR/RID/ADN Limited quantities (LQ) LExcepted quantities (EQ) Transport category Tunnel restriction code D IMDG Limited quantities (LQ) LiL Excepted quantities (LQ) Lic Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity	14.4 Packing group ADR/RID/ADN, IMDG, IATA	Void
Danger code (Kemler): EMS Number: Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity abov 1 litre: Category B. For WASTE AEROSOLS: Categor C, Clear of living quarters. Segregation Code Segregation Code Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with capacity above 1 litre: Segregation as for the appropriat subdivision of class 2. For WASTE AEROSOLS with capacity above 1 litre: Segregation as for the appropriat subdivision of class 2. For WASTE AEROSOLS Segregation as for the appropriate subdivision of class 2. 14.7 Transport in bulk according to Anne x II of Marpol and the IBC Code Transport/Additional information: ADR/RID/ADN Limited quantities (LQ) Linited quantities (EQ) Transport category Transport category 1 Code: E0 Not permitted as Excepted Quantity ILD IMDG Limited quantities (LQ) Linited	14.5 Environmental hazards: Marine pollutant:	No
Danger code (Kemler): EMS Number: Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity abov 1 litre: Category B. For WASTE AEROSOLS: Categor C, Clear of living quarters. Segregation Code Segregation Code Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with capacity above 1 litre: Segregation as for the appropriat subdivision of class 2. For WASTE AEROSOLS with capacity above 1 litre: Segregation as for the appropriat subdivision of class 2. For WASTE AEROSOLS Segregation as for the appropriate subdivision of class 2. 14.7 Transport in bulk according to Anne x II of Marpol and the IBC Code Transport/Additional information: ADR/RID/ADN Limited quantities (LQ) Linited quantities (EQ) Transport category Transport category 1 Code: E0 Not permitted as Excepted Quantity ILD IMDG Limited quantities (LQ) Linited	14.6 Special precautions for user	Warning: Gases.
EMS Number: Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Categor C, Clear of living quarters. Segregation Code SG69 For AEROSOLS with a maximum capacity of litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS with capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. 14.7 Transport in bulk according to Anne x II of Marpol and the IBC Code Transport/Additional information: ADR/RID/ADN Limited quantities (LQ) Limited quantities (EQ) Transport category 2 Tunnel restriction code D IMDG Limited quantities (LQ) Lim		-
SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Categor C, Clear of living quarters. Segregation Code SG69 For AEROSOLS with a maximum capacity of litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with capacity above 1 litre: Segregation as for the appropriat subdivision of class 2. For WASTE AEROSOLS Segregation as for the appropriate subdivision of class 2. 14.7 Transport in bulk according to Anne x II of Marpol and the IBC Code Not applicable. Transport/Additional information: ADR/RID/ADN Limited quantities (LQ) Limited quantities (EQ) Not permitted as Excepted Quantity Transport category Tunnel restriction code D IMDG Limited quantities (LQ) Limited quantities (EQ) Limited quantities (EQ) Not permitted as Excepted Quantity	EMS Number:	F-D,S-U
SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Categor C, Clear of living quarters. Segregation Code SG69 For AEROSOLS with a maximum capacity of litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with capacity above 1 litre: Segregation as for the appropriat subdivision of class 2. For WASTE AEROSOLS Segregation as for the appropriate subdivision of class 2. 14.7 Transport in bulk according to Anne x II of Marpol and the IBC Code Not applicable. Transport/Additional information: ADR/RID/ADN Limited quantities (LQ) Limited quantities (EQ) Not permitted as Excepted Quantity Transport category Tunnel restriction code D IMDG Limited quantities (LQ) Limited quantities (EQ) Limited quantities (EQ) Not permitted as Excepted Quantity	Stowage Code	SW1 Protected from sources of heat.
Marpol and the IBC Code Transport/Additional information: ADR/RID/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Limited quantities (LQ) IL Code: E0 Not permitted as Excepted Quantity D IMDG Limited quantities (LQ) Limited quantities (EQ) Not permitted as Excepted Quantity	Segregation Code	litre: Category A. For AEROSOLS with a capacity abov 1 litre: Category B. For WASTE AEROSOLS: Categor C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with capacity above 1 litre: Segregation as for the appropriat subdivision of class 2. For WASTE AEROSOLS
Transport/Additional information: ADR/RID/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Limited quantities (LQ) Limited quantities (LQ) Limited quantities (EQ) Not permitted as Excepted Quantity 1L Code: E0 Not permitted as Excepted Quantity		
ADR/RID/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ) Limited quantities (LQ) Excepted quantities (EQ) IL Code: E0 Not permitted as Excepted Quantity 1L Code: E0 Not permitted as Excepted Quantity	-	гостаррисавие.
Limited quantities (LQ) Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity Transport category Tunnel restriction code D IMDG Limited quantities (LQ) Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity		
Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity Transport category Tunnel restriction code D IMDG Limited quantities (LQ) Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity		1L
Transport category Tunnel restriction code D IMDG Limited quantities (LQ) Excepted quantities (EQ) Not permitted as Excepted Quantity 1L Code: E0 Not permitted as Excepted Quantity		
Transport category Tunnel restriction code D IMDG Limited quantities (LQ) Excepted quantities (EQ) Not permitted as Excepted Quantity	(
Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (EQ) Not permitted as Excepted Quantity	Transport category	- · · · · · · · · · · · · · · · · · · ·
Limited quantities (LQ) Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity	Tunnel restriction code	
Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity	IMDG	
Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity	Limited quantities (LQ)	1L
Not permitted as Excepted Quantity	Excepted quantities (EQ)	Code: E0
UN "Model Regulation": UN 1950 AEROSOLS, 2.1	- •	Not permitted as Excepted Quantity
	UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Revision: 06.03.2018 Printing date 06.03.2018 Version number 20

Trade name: Rust Shock Spray

(Contd. of page 7)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Department issuing SDS: Product Safety department.

· Contact:

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.