Printing date 08.05.2015 *Version number* 24 *Revision:* 08.05.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Kettenspray

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Lubricant

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

EUROPART Holding GmbH

· Martinstraße 13

· 58135 Hagen-Haspe

· Tel.: +49 2331 3564 0

Telefax: +49 2331 3564 91499 E-Mail: info@europart.net Internet: www.europart.net

· 1.4 Emergency telephone number:

· +44 (171) 635 91 91

Further information obtainable from:

EUROPART Holding GmbH Abteilung Betriebssicherheit

Tel.: +49 2331 3564 4403 (Mo-Fr 8:00-16:00) Tel.: +49 2922 893 2515 (Mo-Fr 8:00-16:00)

Telefax: +49 2331 3564 94400

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2

GHS07

Skin Irrit. 2 H315 Causes skin irritation.

H319

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Causes serious eye irritation.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

*

F+; Extremely flammable

R12: Extremely flammable.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Harmful: may cause lung damage if swallowed.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

(Contd. of page 1)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.05.2015 *Version number* 24 *Revision:* 08.05.2015

Trade name: Kettenspray

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation. H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501 Dispose of contents/container to hazardous or special waste collection point.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

 $\cdot \textit{\textbf{Description:}} \ \textit{Mixture of substances listed below with nonhazardous additions.}$

· Dangerous components:		
CAS: 75-28-5 EINECS: 200-857-2	isobutane F+ R12	20-25%
Reg.nr.: 01-2119485395-27-xxxx CAS: 74-98-6	V - 1	10-20%
EINECS: 200-827-9	<i>propane → F+ R12</i>	10-20/0
Reg.nr.: 01-2119486944-21-xxxx	🏇 Flam. Gas 1, H220; Press. Gas C, H280	
CAS: 106-97-8 EINECS: 203-448-7	<i>butane F</i> + <i>R</i> 12	2.5-10%
Reg.nr.: 01-2119474691-32-xxxx	🚸 Flam. Gas 1, H220; Press. Gas C, H280	
	Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes Xn R65; Xi R38; F R11; N R51/53 R67	2.5-10%
	♦ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ Skin Irrit. 2, H315; STOT SE 3, H336	

(Contd. on page 3)

Printing date 08.05.2015 Version number 24 Revision: 08.05.2015

Trade name: Kettenspray

	(Co	ontd. of page 2)
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane Xn R65; Xi R38; F R11; N R51/53 R67	2.5-10%
	Flam. Liq. 2, H225; Sap. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	
EINECS: 263-093-9	Calciumpetroleumsulfonat Xi R38 R52 ◆ Skin Irrit. 2, H315	1.0-2.5%
CAS: 68608-26-4 EC number: 301-210-8	Sufonic acids, alkane, sodium salts Xi R41 Eximple Description Sufonic acids, alkane, sodium salts Xi R41 Eximple Description Sufonic acids, alkane, sodium salts	1.0-2.5%

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately remove any clothing soiled by the product.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

(Contd. on page 4)

Printing date 08.05.2015 Version number 24 Revision: 08.05.2015

Trade name: Kettenspray

(Contd. of page 3)

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

• **6.4 Reference to other sections** See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin and eyes.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Recommended filter device for short term use: Filter AX

(Contd. on page 5)

Printing date 08.05.2015 *Version number* 24 *Revision:* 08.05.2015

Trade name: Kettenspray

· Protection of hands:

(Contd. of page 4)



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.45 mm

Penetration time of glove material

 \geq 240 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol
Colour: Yellow
• Odour: Petrol-like

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· Flash point: Not applicable, as aerosol.

· Ignition temperature: >200 °C

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapour

mixtures are possible.

• **Density at 20 °C:** 0.68593 g/cm³

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

 Organic solvents:
 52.8 %

 VOC (EC)
 361.9 g/l

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Aldehyde

(Contd. on page 6)

Trade name: Kettenspray

Carbon monoxide and carbon dioxide

(Contd. of page 5)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative LC50/4 h 130 mg/l (rat)

75-28-5 isobutane

Inhalative LC50/4 h > 50 mg/l (rat)

74-98-6 propane

Inhalative LC50/4 h 20 mg/l (rat)

106-97-8 butane

Inhalative LC50/4 h 658 mg/l (rat)

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

 Oral
 LD50
 >5840 mg/kg (rat)

 Dermal
 LD50
 >2920 mg/kg (rat)

 Inhalative
 LC50/4 h
 >23.3 mg/l (rat)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane

 Oral
 LD50
 >5840 mg/kg (rat)

 Dermal
 LD50
 >2920 mg/kg (rat)

 Inhalative
 LC50/4 h
 <25.2 mg/l (rat)</td>

Calciumpetroleumsulfonat

Oral LD50 >2000 mg/kg (rat)

68608-26-4 Sufonic acids, alkane, sodium salts

Oral LD50 >5000 mg/kg (rat)

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitisation: No sensitising effects known.
- · Additional toxicological information: Vapours have narcotic effect.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

EC50/48 h | 3 mg/l (daphnia)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane

EC50/48 h | 3 mg/l (daphnia)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

(Contd. on page 7)

Version number 24 Revision: 08.05.2015 Printing date 08.05.2015

Trade name: Kettenspray

(Contd. of page 6)

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · European waste catalogue
- 16 05 04 gases in pressure containers (including halons) containing dangerous substances

15 01 04 metallic packaging

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informat	ion	
· 14.1 UN-Number		
· ADR, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name		
$\cdot ADR$	UN1950 AEROSOLS	
· IMDG	AEROSOLS	
· IATA	AEROSOLS, flammable	
· 14.3 Transport hazard class(es)		
· ADR		
· ·		
· Class	2 5F Gases.	
· Label	2.1	
· IMDG, IATA		
· Class	2.1	
Label	2.1	
14.4 Packing group		
· ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards:		
· Marine pollutant:	No	
· 14.6 Special precautions for user	Warning: Gases.	
Danger code (Kemler):	-	
	(Contd. on	page

Printing date 08.05.2015 Version number 24 Revision: 08.05.2015

Trade name: Kettenspray

	(Contd. of	page
· EMS Number:	F-D,S-U	
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:		
· ADR		
· Limited quantities (LQ)	1L	
\cdot Excepted quantities (\widetilde{EQ})	Code: E0	
	Not permitted as Excepted Quantity	
Transport category	2	
· Tunnel restriction code	D	
· IMDG		
· Limited quantities (LQ)	1L	
· Excepted quantities $(\widetilde{E}Q)$	Code: E0	
· · · · · - ·	Not permitted as Excepted Quantity	

UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

· UN ''Model Regulation'':

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation. H318

Causes serious eye damage.

- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- R11 Highly flammable.
- R12 Extremely flammable.
- R38 Irritating to skin.
- R41 Risk of serious damage to eyes.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R52 Harmful to aquatic organisms.
- R65 Harmful: may cause lung damage if swallowed.
- R67 Vapours may cause drowsiness and dizziness.

· Abbreviations and acronyms:

 $RiD: \ R\`e glement\ international\ concernant\ le\ transport\ des\ marchandises\ dangereuses\ par\ chemin\ de\ fer\ (Regulations\ Concerning\ the\ International\ Transport\ of\ Dangerous\ Goods\ by\ Rail)$

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 9)

Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.05.2015 Version number 24 Revision: 08.05.2015

Trade name: Kettenspray

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1 Flam. Aerosol 1: Flammable aerosols, Hazard Category 1 Press. Gas C: Gases under pressure: Compressed gas Flam. Liq. 2: Flammable liquids, Hazard Category 2 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

* Data compared to the previous version altered.

(Contd. of page 8)